
SKILL LEVEL



multisized pattern...sizes 6/8/10/12/14/16 /18/20/22/24/26 all together!


www.hotpatterns.com

patterns so hot they're smokin'...



HotPatterns & fabric.com exclusive download

Sporty Sarong-Short




The sweetest little sporty-femme shorts, designed for medium-to-lightweight fluid or drapey fabrics like crinkled gauze, hammered satin, washed linen or voile, crepe, or rayon. Pull-on, slightly flared shorts have a narrow elastic waistband, and a flared, tie-front sarong-style skirt attached through the back waist seam. Shorts and sarong overlay finish at mid-thigh with a narrow hem.


This is the perfect piece for all your summer sports and pastimes...jogging, biking, sailing, tennis, hiking or yoga. You'll also love these worn with a simple tank or T-shirt as an easy beach or pool-side cover-up.


fold

Hot Patterns & fak

exclusive free down sporty sarong-should be sarong back out 1 on fold in fak







Hot Latterns & fabric. exclusive free download sporty sarong-short cut 1 pair in fabric sarong front

13 SZEZZ SIZE 26 SIZE 20 SIZE 18 SIZE 16 SIZE 14 SIZE 12 SIZE 10

oric.com

nload ort

oric





Hot Patterns & fabric.com

exclusive free download sporty sarong-skirt instructions page 1 of 2

SEAM ALLOWANCES & OTHER INFO

Seam allowances are 3/8" or 1cm wide; all seams are sewn right sides together unless otherwise stated.

The waist of the short is finished with a separate elastic casing; the bottom edges of the shorts & the sarong overlay are finished with a narrrow hem.


Skills needed include: making & applying an elastic waist casing; working a narrow hem.

ABOUT THIS STYLE

This skirt is an eight-gore, elastic waist pull-on style with arelaxed fit & flare silhouette.


Oh yes, as always, make & fit a muslin before you cut into your fabric...in this case, use a cheap fabric with a similar drape to your chosen fabric.

SUGGESTED CUTTING LAYOUT FOR THE SKIRT fold fabric in half, with selvedge to selvedge for this layout




FABRIC & NOTIONS REQUIRED

All sizes need around 2 3/4 yards/ 250 cm of 60"/150cm wide fabric for this sarong-shorts. You'll also need enough 1/2" or 1.25 cm wide elastic to circle your waist.



1b Hem the sarong...start at the top edges, at the side seam (you'll leave the top edge along the back unhemmed, because that's where you'll attach the sarong to the shorts) and press the cut edges under a scant 1/8" or 3mm, then press this folded edge under another 1/4" or 7mm.


Work along the top edges of the fronts, the angled edges of the tie, the front edges of the sarong wrap and along the bottom edges of the sarong.



			1				
(0	\leftarrow	\bigcirc I					
7	7	,,		∞	(0		
 	•	•				 	
Ш	Ш	Ш	Ш	Ш	Ш		
N	N	N	N	N	N		
	-	-	-	-			
S	S	S	S	S	S		



THE SERVICE STANS




Hote


2a

Prepare the shorts...join the shorts fronts along the center front seams; join the shorts backs along the center back seams.


please note you will probably wish to tape theese crotch seams as you stitch...this will stop them from distorting. Press all these seams open.



2b Join the shorts fronts to the shorts back along the side seams; then along the inside leg seams. Press the seams open.




Hem the shorts legs...use the same method you used to hem the sarong overlay in step 1b. Press flat.



4a

Time to prepare the elastic casing & complete the sarong-shorts.

Join the elastic casing strip at the short ends to create a long loop. Press the short seam open, then fold in half lengthways and press along the foldline (that's the dashed line marked on the pattern).




4b

Matching the seam of the elastic casing to the center back seam of the shorts, and sewing through all thicknesses, join the bottom edges of the elastic casing to the waist edge of the sarong-shorts.

Make sure that you leave the front of the sarong and the ties free from this seam, or you won't be able to tie it!

Leave an opening along this waist seam, about 2" or 5cm long.



4Cut your elastic so it measures the same as your waist. Push a large safety pin through the elastic, then use this to thread the elastic through the waist channel.

With the elastic ends through, join the ends,then close up the 2" or 5cm opening along the waist casing stitchline.

Now try on your gorgeous new sarong-short, and knot the tie at the front ... don't you look fabulous?

Hot Patterns & fabric.com

exclusive free download sporty sarong-short ealstic casing cut 1 on fold in fabric

Hot Patterns & fabri

PrintTemp -- cexclusive free downloa

sporty sarong-short short front cut 1 pair in fabric

S1ZE 6 S1ZE 8 S1ZE 10 S1ZE 12

Patterns & fabric.com

exclusive free download sporty sarong-short short back cut 1 pair in fabric

c.com

d

